

GRIPline RS

PROFESSIONAL FRAME

- Rim clamping up to 30"
- Double arm/disk bead breaker system, powered by motoinverter
- Bead breaker disks' power 6860 Nm (700 kg)
- Wheel positioning through motorized clamping chuck and laser pointers (patented)
- Operated by pedal and control console with joysticks
- Reinforced chassis and tower
- Patented ultra -quick wheel clamping system, through cone and shaft with lock nut
- Double rotation speed INVERTER system, both direction
- Equipped with lifter, lifting capacity max 80 kg
- Equipped with bead pressing arm, complete with self-storage function
- Locking system for total stiff locking of horizontal and operating arm



Made in Italy

PRODUCT NUMBER / DESCRIPTION

6050 GRIP RS
Power supply: single-phase
220v - 50/60Hz

6051 GRIP RS
+ INFLATING TUBELESS KIT
Power supply: single-phase
220v - 50/60Hz

DATASHEET



Working pressure
8 - 10 bar



Rim clamping
range 12" - 30"



Max tire width 16"
(406 mm)



Maximum tire diameter
1200 mm



Rotation speed
7 - 16 rpm



Weight 672 kg



Dimensions (H x D x L)
1750 x 1850 x 1800 mm



Cardboard box packaging (H x D x L)
1880 x 1150 x 1420 mm

STANDARD ACCESSORIES



n. 2 rubber protection
for clamping chuck



Plastic tire lever



Kit of Nylon tools
protection



n. 2 plastic protection for
lock nut centering cone



Bead pressing device

EXTRA OPTIONS FOR TIRE CHANGERS GRIP RS



ART. 6226

- Kit of nylon plastic protections mounting/demounting tools for GRIP RS



ART. 6227

- Kit of 10 rubber protection for clamping chuck



ART. 6228

- Plastic protection for lock nut centering cone set of 10



ART. 6229

- Plastic tire lever. To be used during tire demanding in accordance with the WDK procedure



ART. 6230

- Kit of four rubber protection for alloy wheels with exposed spokes



ART. 6231

- Nylon cone for special LAMBORGHINI wheels, center hole diameter from Ø 55 - 85 mm




ART. 6232

- Nylon cone for special PORSCHE wheels, allows clamping wheels with center hole diameter from Ø 60 to 85 mm.



ART. 6233

- Nylon cone for special BMW wheels, allows clamping wheels with center hole diameter from Ø 55 to 70 mm.



ART. 6234

- Double face cone for light trucks, allows clamping VANs and LCVs wheels with center hole diameter from 75 to 145 mm.



ART. 6235

- Truck cone kit, allows clamping VANs and LCVs wheels with center hole diameter from 120 to 190 mm.



ART. 6236

- Truck cone kit, allows clamping VANs and LCVs wheels with center hole diameter from 190 to 223 mm.



ART. 6237

- Wheel clamping adaptor for reverse mounted wheels and wheels with no center hole



ART. 6238

- Cone for steel rims with low thickness and center hole diameter from 75 to 120 mm



ART. 6244

- Bead pressing device



ART. 6245

- Higher bead pressing device