

VISION^{line} 8CCD PREMIUM

- Digital 20° CCD cameras with advanced sensor technology
- 4 precision jaws for all standard rims for an accurate closing
- 8 CCD sensors for a complete side to side measuring
- Two-phase EASY rolling runout compensation, 30° front, 30° back
- Crushproof aluminium sensors
- A user-friendly software with graphics and animation guides the operator during alignment
- Convergence adjustment program with steered wheels for a better access to the vehicle's mechanics
- Immediate measurement of parameters software
- Suitable for any light condition
- Complete radio transmission. Frequency band 433 MHz.
- Double database for customer and manufacturer.
- 27" monitor - PC - Multifunction color printer
- Measuring sensors with intelligent charging system
- Cables included



Made in Italy

PRODUCT NUMBER / DESCRIPTION

4000	VISION 8 CCD PREMIUM Power supply: single-phase 220v - 50/60Hz
-------------	---

DATASHEET



Easy run out 30°



Weight 80 kg



Dimensions (H x D x L)
1600 x 980 x 800 mm



Wheel clamps
10" - 22"


MAXIMUM MEASURING RANGE

Total convergence	18°
Single convergence	9°
Chamber	10°
Setback	9°
Incidence	22°
Tilt steering axis	22°
Toe-out on turns	20°
Axis offset	9°

STANDARD ACCESSORIES



4 precision MULTIFIT jaws
for all standard rims



Special endpins for
MULTIFIT jaws, kit of 16



Set of 2 aluminium turnable
plated with pads 450x450 thick
50 mm capacity 1000 kg



Steering wheel lock



Brake blocks

EXTRA OPTIONS FOR WHEEL ALIGNMENT VERSION 8 CCD PREMIUM



ART. 4201

- Set of 2 aluminium turning plates with pads 450x450 mm thickness 50 mm.
- Capacity 1000 KG



ART. 4214

- Steering wheel level for alignment



ART. 371

- Serie 4 cavalletti per assetto ruote



ART. 4204

- Database uploading for VISION 8CCD PREMIUM



ART. 4202

- Wheel fastener extension set, up to 28", (for each MULTIFIT jaw)



ART. 4205

- Set of 4 clamps ProClamp PLUS



ART. 4216

- Kit of 3 extensions 4" for ProClamp PLUS