

GRIP24

Leverless
Inverter
Iron Arm



- Turntable tightens up to 26"
- Long-lasting jaws made of hardened steel
- "Easy Access" extractable pedal box for quick service
- Reinforced chassis and tower
- Double rotation speed by pedal with INVERTER
- Pneumatic lifting of the tool
- Bead breaker double effect. Cylinder Ø 200 mm
- Pneumatic tilting tower
- Adjustable bead breaker shovel angle
- POWER OUT patented system for granting no BB shovel stuck into the rim
- Tire inflation by pedal
- Side arm for standard RUN FLAT tires
- Standard equipped with LEVERLESS system

DATASHEET

- Working pressure: 8 - 10 bar
- Turntable tightening: outward 10" - 24" inward 12" - 26"
- Tire width: min. 3" - max 16"
- Maximum tire diameter: 1100 mm
- Rotation speed: 7 - 16 rpm
- Weight: 379 kg
- Dimensions (H x D x L): 1890 x 1590 x 2040 mm
- Cardboard box packaging: 1880 x 1150 x 1430 mm

STANDARD EQUIPMENT



- Kit of 4 plastic protection jaws



- Mounting lever 500 mm



- N. 3 mounting tool cover



- N. 3 demounting head tongue protection



- Plastic protection suitable for bead breaker

CODE

6012/ML

DESCRIPTION

GRIP 24
Power supply:
single-phase 230V - 50/60Hz

EXTRA OPTIONS FOR TIRE CHANGERS GRIP 24



ART. 6221

- Kit of 4 rubber costed jaw protectors



ART. 6223

- Plastic protection suitable for bead breaker



ART. 6240

- Kit of 10 demounting head tongue protection



ART. 6241

- Kit of 10 mounting tool cover



ART. 6244

- Bead pressing device




ART. 6245

- Higher bead pressing device



ART. 6247

- Adjusting device for leverless tool



ART. 6249

- Roller board



ART. 6254

- Inflating tubeless kit