










GRIP52SUPER



- Hydraulic spindle with adjustable pressure
- Double speed and reversible rotation
- Hydraulic fitting carriage sliding
- Control unit ergonomically designed
- Jaws with different rim's grip to fit all models
- Quick rotation system for operating arm
- Bead breaking force 26500 Nm

DATASHEET

	Spindle tightening inward: 14" - 42"
	Tire width: 1150 mm - 45"
	Maximum tire diameter: 2300 mm - 91"
	Maximum tire weight: 2000 kg
	Rotation speed: 4,5 - 9 rpm
	Engine power: 2,2 - 3 kw
	Weight: 880 kg
	Dimensions (H x D x L): 1750 x 2150 x 2500 mm
	Cardboard box packaging: 1025 x 2250 x 1950 mm



STANDARD EQUIPMENT



- Mounting lever 500 mm
- Long mounting lever
- Rim clamp for industrial wheels

CODE

7005

DESCRIPTION

GRIP 52 SUPER
Power supply:
3-phase 400V - 50/60Hz

EXTRA OPTIONS FOR TIRE CHANGERS GRIP 52 SUPER



ART. 7052

- Protective jaws for aluminum rims, set of 4



ART. 7054

- Clamping extension jaw, set of 4



ART. 7055

- Rim clamp for aluminum rims



ART. 7057

- Rims adaptors kit.
Central hole 80 mm



ART. 7050

- Inflation cage for truck tires

INFLATION CAGE FEATURES

Weight: 166 kg

External dimensions (H x D x L): 1580 x 1600 x 800 mm

Internal dimensions (H x D x L): 1500 x 1500 x 700 mm

Maximum tire diameter: 1500 mm

Maximum tire width: 700 mm