

# VISION 46

Truck and cars  
Radio transmission  
Accelerometer  
Lithium battery



• Tablet or PC not included in the kit

- Maximum steering angle 20°
- 4 precision jaws for all standard rims for an accurate closing
- 8 CCD sensors for a complete side to side measuring
- Two-phase EASY rolling runout compensation, 30° front, 30° back
- Ultralight crushproof aluminium sensors
- A user-friendly software with graphics and animation guides the operator during alignment
- Specific software for Truck adjustments with customized vehicle's selection
- Toe adjustment program with steered wheels for a better access to the vehicle's mechanics (only auto mode)
- Immediate measurement of parameters software
- Suitable for any light condition
- Complete radio transmission. Frequency band 2.4 Ghz
- Double database for customer and manufacturer.
- Measuring sensors with intelligent charging system
- Long lasting lithium batteries
- Direct measurement of wheelbase and wheel track
- Consistent with Windows 7 / 8 / 10 32 and 46 Bit
- Database updated with over 95.000 vehicles

## DATASHEET

- Easy run out: 45°
- Weight: 30 kg
- Cardboard box packaging: 960 x 660 x 1160 mm
- Wheel clamps: 10" - 24"

### MAXIMUM MEASURING RANGE

Total toe	18°
Single toe	9°
Camber	10°
Wheel setback	9°
Caster	22°
Steering axis inclination	22°
Toe-out on turns	20°
Axis offset	9°

CODE	DESCRIPTION
4006	VISION 46 Power supply: single-phase 230V - 50/60Hz

## STANDARD EQUIPMENT



- N. 4 precision jaws for all standard rims



- Triple set of endpins for jaws,  
N. 16 pcs length 45 mm  
N. 16 pcs length 81,5 mm  
N. 16 pcs length 120 mm



- Steering wheel lock
- Brake blocks

## EXTRA OPTIONS FOR WHEEL ALIGNMENT VISION 46



**ART. 4209**

- Database uploading for VISION 46



**ART. 4213**

- Set of 2 turning plates for truck
- Capacity 6000 kg



**ART. 4214**

- Steering wheel level for alignment



**ART. 4217**

- Adaptor rod for semitrailers